

VERSATRUK 1500

Product Code: LTEPF41150

The Liftek VersaTruk 1500 Fully Electric Pallet Truck with built-in Lithium-ion battery offers a cost-effective handling solution with maximum flexibility.

VERSATRUK 1500 QUICK SPECS:

Weight = 120 kg / Capacity = 1500 kg:

560 mm x 1150 mm - OTHER FORK SIZES AVAILABLE

KEY FEATURES

- ✓ Fully Electric, with Electric Lift and Forwards/Backwards Drive
- ✓ Removable Lithium-Ion Battery
- ✓ Approx. 5.5hrs Constant Usage w/ Single Battery / 11hrs w/ 2 Batteries
- Only weighs 120kg!
- 12 Month Warranty as Standard



CALL US TODAY AND TALK TO OUR TEAM OF EXPERTS



Product Code: LTEPF41150



Why the VersaTruk 1500?

The VersaTruk 1500 brings maximum flexibility in configurations for every application, from occasional usage to heavy duty. Featuring a two power slot design, VersaTruk offers the option of two 24V/20Ah batteries to maximize runtime for full-time applications. The standard single-battery setting comes with a portable storage container to keepeverything easily accessible on the go. Its versatility makes FlexiTruk an all-rounder, perfect for diverse tasks in the most cost effective way.



Heavy-duty
Estimated real life working time: 11hrs



Occasional usage Estimated real life working time: 5.5hrs



CALL US TODAY AND TALK TO OUR TEAM OF EXPERTS



SHS HANDLING SOLUTIONS

Experts in handling solutions


Product Code: LTEPF41150


Distinguishing mark	1.1	Manufacturer			Liftek
	1.2	Model designation			LTEPF41150
	1.3	Drive unit			Electric
	1.4	Operator type			Pedestrian
	1.5	rated capacity	Q	kg	1500
	1.6	Load center distance	С	mm	600
	1.8	Load distance, centre of drive axle to fork	Х	mm	950
	1.9	Wheelbase	у	mm	1180
Service weight	2.1	Service weight		kg	120
	2.2	Axle loading, laden front/rear		kg	480/1140
	2.3	Axle loading, unladen front/rear		kg	90/30
	3.1	Tyre type			Polyurethane
	3.2	Tyre size, front		mm	210x70
Tyres/chassis	3.3	Tyre size, rear		mm	Ф80х60(Ф74х88)
	3.4	Additional wheels		mm	Φ74x30 optional
	3.5	Wheels, number front/rear (x=drive wheels)		mm	1x 2/4 (1x 2/2)
	3.6	Tread, front	b10	mm	_
	3.7	Tread, rear	b11	mm	535/410
Dimensions	4.4	Lift height	h3	mm	105
	4.9	Height drawbar in driving position min./max.	h14	mm	750/1190
	4.15	Lowered height	h13	mm	82
	4.19	Overall length	11	mm	1550
	4.20	Length to face of forks	12	mm	400
	4.21	Overall width	b1/b2	mm	695/590
	4.22	Fork dimensions	s/e/l	mm	55/150/1150
ā	4.25	Distance between fork-arms	b5	mm	685/560
	4.32	Ground clearance, center of wheelbase	m2	mm	25
	4.34.1	Aisle width for pallets 1000×1200 crossways	Ast	mm	2160
	4.34.2	Aisle width for pallets 800×1200 crossways	Ast	mm	2025
	4.35	turning radius	Wa	mm	1360
<u></u>	5.1	Travel speed, laden/unladen		km/h	4/4.5
Performance data	5.2	Lifting speed, laden/unladen		m/s	0.017/0.020
	5.3	Lowering speed, laden/unladen		m/s	0.046/0.058
	5.8	Max. gradeability, laden/unladen		%	5/16
	5.10	Service brake			Electromagnetic
Electric-engine	6.1	Drive motor rating S2 60 min		kW	0.75
	6.2	Lift motor rating at S3 15%		kW	0.5
	6.4	Battery voltage/nominal capacity		V/Ah	24/20
	6.5	Battery weight		kg	5
Addition E	8.1	Type of drive unit		-	DC
	10.5	Steering design			Mechanical
	10.7	ound pressure level at the driver's ear		dB(A)	<74
				, ,	

If there are improvements of technical parameters or configurations, no further notice will be given. The diagram shown may contain non-standard configurations.

CALL US TODAY AND TALK TO OUR TEAM OF EXPERTS







No.	Optional items	F4			
1.1	Fork dimension	●1150*560○900*560○1000*560○1220*560○1350*560○1500*560 ○900*685○1000*685○1150*685○1220*685○1350*685○1500*685			
1.3	Fork lowered height	●80			
1.6	Drive cover off the ground	●45mm (CE)○65mm (Non CE)			
2.1	Load wheel type	 Double Single 			
2.2	Load wheel material	 Polyurethane 			
2.3	Drive wheel material	 ◆Polyurethane 			
2.7	Battery capacity	●20AH×1 (with a storage container) ○20AH×2 ○20AH×3 ○20AH×4			
2.8	Charger	●24V-4A External ○24V-10A External			
2.9	Battery indicator	●Without time			
2.16	handle head type	●Hands big handle head ○Hands small handle head			
3.3	Castor wheels	No○Yes and not customized			
3.12	Hummer	●Yes and not customized			
3.16	Vertical handler working	●Yes and not customized			
4.8	Drive assembly	●Yes and not customized			
Note: ●Standard ○ Optional - Inconformity					

CALL US TODAY AND TALK TO OUR TEAM OF EXPERTS